

Carbide Tipped SDS-MAX Drill Bits, Core Bits and Chisels

SDS MAX Drill Bits



Order No.	Bit Diameter	Useable Length	Overall Length
MP 240	1"	8"	13-1/4"
MP 435	1"	11-1/2"	17"
MP 495	1-1/8"	11-1/2"	17"
MP 540	1-1/4"	11-1/2"	17"
MP 600	1-3/8"	11-1/2"	17"
MP 690	1-1/2"	11-1/2"	17"
MP 510	1-1/8"	17"	22-1/2"
MP 555	1-1/4"	17"	22-1/2"
MP 650	1-3/8"	17"	22-1/2"
MP 705	1-1/2"	17"	22-1/2"
MP 525	1-1/8"	30-3/4"	36-1/4"
MP 630	1-3/8"	30-3/4"	36-1/4"

SDS MAX Core Bits



Order No.	Bit Diameter	Overall Length
SDS-Max Core Bit Adapter		
PAT-SMAX		
PC-9888	1"	6"
PC-9999	1-1/8"	6"
PC-9100	1-1/4"	6"
PC-9110	1-1/2"	6"
PC-9120	1-3/4"	6"
PC-9130	2"	6"
PC-9140	2-1/2"	6"
PC-9145	2-3/4"	6"
PC-9150	3"	6"
PC-9160	3-1/2"	6"
PC-9170	4"	6"
PC-9172	4-1/2"	6"
PC-9173	5"	6"
PC-9174	6"	6"
PC-9200	Pilot Drill for 1-1/2" thru 6" Core Bits	
PDE-6	6" OAL Core Bit Extension	
PDE-12	12" OAL Core Bit Extension	
T-750	Threaded Coupler for All Core Bits	

SDS MAX Chisels



Order No.	Type	Width	Length
CS 5801	Flat Chisel	1"	12"
CS 5803	Flat Chisel	1"	18"
CS 5805	Moil Point	-	12"
CS 5807	Moil Point	-	18"
CS 5809	Scaling Chisel	2"	12"
CS 5811	Scaling Chisel	2"	18"
CS 5812	Scaling Chisel	3"	12"
CS 5813	Slotting Tool	1-1/8"	12"
CS 5815	Seam Tool	1-1/8"	12"
CS 5816	Clay Spade	4-1/2"	15-1/2"
CS 5817	Ground Rod Driver	-	10-1/2"
CS 5818	Bushing Tool	-	9-1/2"
CS 5818 CB	Carbide Tip Bush Tool	-	9-1/2"
CS 5820	Asphalt Cutter	3-1/2"	15-1/2"
CS 5822	Floor Scraper	6"	25"



NOTE: Core Bits require 3 pieces: The Core Bit Adapter or shank, the core bit body, and the pilot drill. The Threaded Coupler is supplied with the adapter at no charge. It is listed as a replacement part should it break.