



Cutter capacity
5" dia.

ECO™-130AK



Triple arbor bearing guidance for drilling up to 5" dia.



Model ECO-130AK

- Strongest magnetic drill press in its class
- Variable-speed and two gears (40-140 and 120-480 RPM)
- Multiple speeds match cutter diameter to correct RPM
- 3¹/₃" stroke with special triple arbor bearing guide
- Powerful, high-torque 16 Amp motor with reverse
- Variable torque control regulates power output
- HD dual-coil magnet has holding strength of 10,560 lbs.
- Drills up to 5" diameter holes with TCT Annular Cutters
- Mechanical slip clutch disconnects the transmission in case of overload
- Automatic lubrication system
- Optional Power Assist to maintain maximum RPM under full load
(Part No. 020.0336)
See page 23 for more information.



Automatic cooling/
lubrication system



Triple arbor bearing guide ensures stability for large-diameter hole drilling.

TEMPTEC™ Magnet **SENORTEC™ System**

See page 2

Ideal for use with large-diameter Tungsten Carbide-tipped (TCT) cutters (see page 22).



Standard equipment includes carrying case, safety chain, carabin hook and allen keys.

Includes one-year warranty



Optional 3/4" arbor adapter, P/N IBK-32/19
Cutter capacity up to 5" dia.

See pages 18-26 for Annular Cutters and Accessories.

Model ECO-130AK

Motor Power	16 Amp / 110 Volt*
Weight	79 lbs.
Hole Capacity	5" dia.
Speeds	40-140 and 120-480 RPM
Magnet Base Size	9 ¹ / ₂ " L x 4 ³ / ₄ " W
Dimensions	26 ¹ / ₄ " H x 13 ³ / ₈ " L x 7 ¹ / ₂ " W
Magnetic Force (1" plate)	10,560 lbs.
Arbor Bore	1 ¹ / ₄ "**
Automatic Lubrication	Included

* 220 Volt / 50 Hz also available ** 3/4" also available, Part No. IBK-32/19
*** Power Assist Part No. 020.0336