



Cutter capacity
1 1/4" dia.

ECO™-32 and ECO™-32AK



Best power-to-weight performance in the industry



Model ECO-32

- Lightweight and portable at only 24 lbs.
- Compact height of 14 1/4" for drilling in tight spaces
- Strong 8.2 Amp double-insulated motor
- High-density dual-coil magnet has holding strength of 3080 lbs.
- Drills up to 1 1/4" diameter holes with Annular Cutters; up to 1/2" with twist drills
- Optional Power Assist to maintain maximum RPM under full load (Part No. 020.0330)

See page 23 for more information.

TEMPTEC™
Magnet

SENSORTEC™
System

See page 2



7 1/2"
stroke



Model ECO-32AK has an automatic cooling/lubrication system built into the arbor.



Standard equipment includes carrying case, safety chain, carabin hook and allen keys.

Includes one-year warranty

With a 1/2" chuck (Part No. IBK-17), these models easily convert to standard drill presses with a 7 1/2" stroke for conventional twist drills.

Model ECO-32 and ECO-32AK

Motor Power	8.2 Amp / 110 Volt*
Weight	24 lbs.
Hole Capacity	1 1/4" dia.
Twist Drill Capacity	1/2" dia.
Speed	450 RPM
Magnet Base Size	6 5/16" L x 3 1/4" W
Dimensions	14 1/4" H x 9 1/2" L x 4 3/8" W
Magnetic Force (1" plate)	3080 lbs.
Arbor Bore	3/4"
Manual Lubrication	Order Model ECO-32
Automatic Lubrication	Order Model ECO-32AK

* 220 Volt / 50 Hz also available ** Power Assist Part No. 020.0330



Cutter capacity up to 1 1/4" dia., stroke: 5 3/4"

Twist drill capacity up to 1/2" dia., stroke: 7 1/2"

See pages 18-26 for Annular Cutters and Accessories.