



ECO™-50 and ECO™-50AK



Lightweight, two-speed high-performance drill



- Drills up to 2" diameter holes with Annular Cutters
- Lightweight and portable at 29 lbs.
- Strong 10.5 Amp motor and two-speed gearbox
- HD dual-coil magnet has holding strength of 3750 lbs.
- Easy "twist and lock" keyless arbor for cutters
- Compact height of 16½" allows drilling in small spaces
- With a ¾" chuck (Part No. IBK-22), these models easily convert to standard drill presses with a 5" stroke for up to 7/8" dia. twist drills
- Optional Power Assist to maintain maximum RPM under full load (*Part No. 020.0330*)

See page 23 for more information.

TEMPTEC™
Magnet

SENORTEC™
System

See page 2

Model ECO-50AK has an automatic cooling/lubrication system built into the arbor.



Model ECO-50 with keyless chuck cutter holder

Standard equipment includes Auto Chuck cutter holder, carrying case, safety chain, carabin hook and allen keys.

Includes one-year warranty



With a ¾" chuck (Part No. IBK-22) or MT2, these models easily convert to standard drill presses with a 5" stroke for conventional twist drills.



Cutter capacity up to 2" dia., stroke: 6"

Twist drill capacity up to 7/8" dia., stroke: 5"

See pages 18-26 for Annular Cutters and Accessories.

Model ECO-50 and ECO-50AK

Motor Power	10.5 Amp / 110 Volt*
Weight	29 lbs.
Hole Capacity	2" dia.
Twist Drill Capacity	7/8" dia.
Speeds	Gear 1: 250, Gear 2: 450 RPM
Magnet Base Size	6½" L x 3½" W
Dimensions	16½" H x 9" L x 6¾" W
Magnetic Force (1" plate)	3750 lbs.
Arbor Bore	¾"
Manual Lubrication	Order Model ECO-50
Automatic Lubrication	Order Model ECO-50AK

* 220 Volt / 50 Hz also available ** Power Assist Part No. 020.0330