

# Pneumatic and Hydraulic Nut Runners

ATEX

*Ideal for turning valves, tightening, tapping, reaming, pipe beveling, expanding and more*



- Worm gear drive provides high torque – up to 554 ft.-lbs.
- Lightweight and reversible
- Compact angle head allows access to confined spaces
- Both Pneumatic and Hydraulic models available
- One-year warranty



Model  
6 1015 0075

Model numbers pictured above (listed from top to bottom): 6 1015 0075 (with male drive), 6 1015 0010 (female), 6 1014 0075 (with male drive)

Available with Male or Female Square Drives, in a variety of sizes



Male Sq. Drive Head  
1/2" or 3/4"



Female Sq. Drive Head  
3/4" or 7/8"  
(7/8" pneumatic only)

## Square Drive Accessories



**6 1015 7030**  
3/4" Male Square Drive with retaining hole  
(included with model numbers 6 1014 0075,  
6 1015 0075 and 6 1016 0075)



**6 1015 7020**  
1/2" Male Square Drive with retaining hole  
(included with model numbers 6 1014  
0099, 6 1015 0099 and 6 1016 0099)

**6 1017 7940**  
3/4" Male Square Drive with retaining pin

**6 1018 7940**  
1/2" Male Square Drive with retaining pin

Pneumatic Nut Runner Model No.	Square Drive F=Female M=Male	Stall Torque at 90 PSI (ft.-lbs.)	Free Speed (RPM)	Load Speed (RPM)	Power (HP)	CFM at 90 PSI	Side to Center Distance (inches)	Length (inches)	Weight (lbs.)	Air Connection (inches)	Hose ID (inches)
6 1014 0010	3/4" F	100	180	100	0.9	42	1	16	10	NPT 3/8	1/2
6 1014 0075	3/4" M	100	180	100	0.9	42	1	16	11	NPT 3/8	1/2
6 1014 0099	1/2" M	100	180	100	0.9	42	1	16	11	NPT 3/8	1/2
6 1015 0010	3/4" F	423	44	22	0.9	45	1	21	10	NPT 3/8	1/2
6 1015 0075	3/4" M	423	44	22	0.9	45	1	21	10	NPT 3/8	1/2
6 1015 0099	1/2" M	423	44	22	0.9	45	1	21	10	NPT 3/8	1/2
6 1016 0010	3/4" F	141	120	67	0.9	42	1	21	10	NPT 3/8	1/2
6 1016 0075	3/4" M	141	120	67	0.9	42	1	21	11	NPT 3/8	1/2
6 1016 0099	1/2" M	141	120	67	0.9	42	1	21	11	NPT 3/8	1/2
6 1017 0010	3/4" F	60	260	125	0.9	46	1	21	11	NPT 3/8	1/2
6 1017 0075	3/4" M	60	260	125	0.9	46	1	21	11	NPT 3/8	1/2
6 1017 0099	1/2" M	60	260	125	0.9	46	1	21	11	NPT 3/8	1/2
6 1021 0010	7/8" F	423	44	22	0.9	45	1	21	11	NPT 3/8	1/2

Hydraulic Nut Runner Model No.	Square Drive F=Female M=Male	Stall Torque at 90 PSI (ft.-lbs.)	Free Speed (RPM)	Load Speed (RPM)	Power (HP)	Oil Flow (GPM)	Oil Pressure (GPM)	Side to Center Distance (inches)	Length (inches)	Weight (lbs.)	Connection Quick Couplers
3 6242 0010*	3/4" F	554	44	22	1.6	4 - 13	1000	1	20	22	1/2" FF
3 6243 0010*	3/4" F	223	44	90	1.6	4 - 13	1000	1	20	22	1/2" FF

\* Also available with 1/2" and 3/4" Male Square Drive