

# Pneumatic and Hydraulic Corner Drills and Drives

## High-torque drilling, reaming and driving units

CORNER DRILLS AND DRIVE UNITS



Model 2 1801 0030

ATEX

### Corner Drills and Bridge Reamers

- Small side-to-side distance for working in tight spaces
- Self-closing roll throttle
- Built-in oiler for motor
- Ideal for bridge reaming and drilling applications
- One-year warranty
- Visit [www.csunitec.com](http://www.csunitec.com) for dimensions

### Slow-speed, High-torque Straight Drive Units



Model 2 2087 0010 with reverse and lever throttle

- Ideal for heavy-duty reaming, tube expanding and tapping
- Perfect for special driving applications, including pipe tapping and valve turning

### Square Drive Accessories

- 2 2089 7020 – 7/8" Male Square Drive to 3/4" Male Square Drive
- 2 2089 7070 – 7/8" Male Square Drive to 1" Male Square Drive
- 6 1016 7940 – 7/8" Male Square Drive to 1" Male Square Drive with retaining pin

Pneumatic Corner Drill Model No.	Morse Taper	Drilling (in steel)	Reaming (in steel)	Tube Rolling Cap.	Torque Output (ft./lbs.)	Load Speed (RPM)	Motor Power (HP)	CFM at 90 PSI	Length	Weight (lbs.)
<b>Nonreversible</b>										
2 1602 0030	#1	5/8"	1/2"	N/A	7	500	0.7	21	12.5"	7
2 1701 0030	#2	7/8"	5/8"	N/A	35	270	1.8	49	20.9"	19
2 1801 0030	#3	1 1/4"	1"	N/A	53	260	2.6	63	22.5"	25
<b>Reversible</b>										
2 2104 0030	#4	2 1/8"	2"	2"	86	180	3.0	71	23.8"	37

Model No. 2 1602 0030 has a 3/8" NPT air inlet. 1/2" (13mm) hose is recommended. All other models have 3/4" NPT air inlet. A 1/2" (13mm) hose is recommended for model 2 1701 0030. A 5/8" (15mm) hose is recommended for models 2 1801 0030 and 2 2104 0030.

Hydraulic Corner Drill Model No.	Morse Taper	Drilling (in steel)	Reaming (in steel)	Tube Rolling Cap.	Torque Output (ft./lbs.)	Load Speed (RPM)	Motor Power (HP)	Oil Flow/PSI	Length	Weight (lbs.)
2 1806 0010	#3	1 1/4"	1"	N/A	60	220	3.8	4 GPM @2000	21"	25

Pneumatic Drive Unit Model No.	Square Drive ID	Torque Output (ft./lbs.)	Load Speed (RPM)	Reversible	Tube Rolling Cap.	Tapping Cap.	Motor Power (HP)	CFM at 90 PSI	Height x Length	Weight (lbs.)
2 2081*	13/16"	413	20	YES	3"	1 1/2"	1.35	53	10.9" x 26.5"	29
2 2087*†	7/8"	413	20	YES	3"	1 1/2"	1.35	53	10.9" x 26.5"	29
2 2088*†	7/8"	138	60	YES	2"	3/4"	1.35	53	10.9" x 26.5"	29

\* The last four digits of the Model No. identify the type of throttle. † Square drive accessories available (see above). Please specify the four digits when ordering: 0010 for Lever Throttle or 0030 for Safety Twist Throttle.