

Pneumatic and Electric Nibblers

Easily cut sheet metal and steel up to 3/8" thick

- Air or electric power is ideal for cutting sheet metal, steel plate, weldments and double sheets
- Two-speed gearbox (model CS-3400-P or -E)
- Head can be rotated to four 90° positions (selected models)
- Cut over 90° bends with optional die
- Maximum cutting capacity:

Mild Steel	Stainless Steel	Aluminum
up to .375"	up to .195"	up to .500"
- Ideal for use in underground storage tank removal, I-beam splitting, plate cutting and more



Model No.	Power	CFM	Working Speed (ft./min.)	Start Hole Dia.	Min. Radius	Strokes per Minute	Max. Sheet Thickness			Weight (lbs.)
							Mild Steel	Stainless Steel	Aluminum	
Electric (110 Volt)										
CS-350-E	12 Amp	-	4	1.25"	.280"	650	.135"	.090"	.135"	7.5
CS-500-E	12 Amp	-	4.5	1.25"	3.125"	600	.197"	.135"	.276"	8.5
CS-700-E	17.4 Amp	-	5	2.75"	5.5"	400	.276"	.197"	.394"	26
CS-3400-E*	17.4 Amp	-	5.2	3"	16"	230 / 370	.375"	.276"	.500"	32
Pneumatic										
CS-350-P	1.5 HP/90 PSI	54	4	1.25"	.280"	530	.135"	.090"	.135"	10
CS-500-P	1.5 HP/90 PSI	54	4.5	1.25"	3.125"	530	.197"	.135"	.276"	10.5
CS-700-P	4 HP/90 PSI	100	5	2.75"	5.5"	340	.276"	.197"	.394"	27
CS-3400-P*	4 HP/90 PSI	100	5.2	3"	16"	210 / 350	.375"	.276"	.500"	32

* 2-speed gearbox

ProLube™ Lubricants ideal for cutting steel, stainless steel and hard metals

Cutting tools work cooler, longer and more efficiently with ProLube™ Lubricants from CS Unitec.

- Improve cutting tool output and performance
- Prolong tool life by reducing friction and wear
- Unique composition provides excellent adhesion to cutting tools for maximum lubrication
- Corrosion inhibitor
- Ideal for saw blades and drill bits
- Non-toxic

ProLube Solid
 CS 7020-013
 1.6 oz. push tube
 CS 7020-000
 14.5 oz. push tube



High film strength – stays on for the cut!



ProLube Liquid
 Water soluble 16:1
 CS 7010-504
 1 gal. bottle



ProLube Paste
 CS 7030-712
 12 oz. tub