

# FINGER BELT SANDER *Variable-speed*

Ideal for angles and tight spaces, as well as pipes and curves. The swivel-mounted arm, with 140° flexibility, reaches into corners, grooves and folds.

The LBS 1105 VE finger belt sander saves time grinding in confined and difficult areas. It uses belt sizes 3/16" to 1-1/8" wide by 21" long. The sanding arm rotates up to 140° for reaching into corners, grooves and folds, including pipes and curves.

The finger sander is ideal for grinding, blending, polishing and deburring ferrous and nonferrous metal. It also works on wood, plastic, fiberglass and other material. Speed is adjustable from 13 to 39 ft./sec.



**LBS 1105 VE with 3/8" sanding arm. Interchangeable 1-1/8" arm shown at right.**



**Finger Belt Sander Accessories**

### Abrasive grinding belt (10/pkg.)

Size	Grit	Part No.
3/16"	60	303.615
3/16"	120	303.623
3/8"	40	257.101
3/8"	60	257.105
3/8"	120	257.102
3/8"	220	257.103

### Surface conditioning belt (3/pkg.)

Size	Grit	Part No.
3/8"	240	318.663
3/8"	400	318.671
1-1/8"	240	318.647
1-1/8"	400	318.655

### SuperPolish Belt (1/pkg.)

For high-gloss polishing, without polishing agents, in two steps

Size	Grit	Part No.
1-1/8"	600	318.132
1-1/8"	1500	318.140

### Optional Equipment

(1) 3/8" sanding arm (curved) – Part No. 256.532

(1) 1-1/8" sanding arm (small roller) – Part No. 255.282

(1) 1-1/8" sanding arm (large roller) – Part No. 258.888



**Narrow filing arm and 140° adjustability allow sanding and grinding in confined and difficult areas.**



### Finger Belt Sander Specifications

**Order Number: LBS 1105 VE**

<b>Belt speeds</b>	13 to 39 ft./sec.
<b>Motor</b>	6.1 AMP
<b>Weight</b>	5.5 lbs.

### Standard Equipment

- (1) 3/8" sanding arm (pointed) – Part No. 256.525
- (1) abrasive belt kit, grits 40/120/220 – 1 set
- (1) side handle – 194.034
- (1) hexagon socket screw key – 115.460



**Standard equipment includes a metal carrying case.**