

Angle Grinders / Sanders with Dust Extraction

L 1506 VV 4" and 4-1/2", Electric
Extremely powerful 11 Amp angle grinder and sander with variable-speed electronic motor. Vacuum port: 1-1/4". Ideal for use with our CS 1225 or CS 1500 Dust Extraction Vacuum (see below).

L 1506 VV AIR 4" and 4-1/2", Pneumatic
Extremely powerful 1 HP angle grinder and sander with 1 HP pneumatic motor. Vacuum port: 1-1/4". Ideal for use with our CS 1225 or CS 1500 Dust Extraction Vacuum (see below).

Vacuum Port: 1-1/4"

L 1506 VV Specifications

	L 1506 VV	L 1506 VV AIR
Max. diameter	4-1/2"	4-1/2"
Speed	2200 - 6800 RPM	6000 RPM
Power	11 Amp	1 HP
Spindle	5/8"-11	5/8"-11
Weight	4 lbs.	4 lbs.
Air consumption	-	33 CFM @ 90 PSI
Air connection	-	1/4"



L 1506 VV with dust extraction (2200 to 6800 RPM)



Stepped Adapter (optional) adapts vacuum port to a 1-1/4" dia. hose
Part Number: 5.453-016



L 1506 VV AIR (6000 RPM)
(Hose not included)



CS 1500



CS 1225

Dust Extraction Vacuums for Tools

CS Unitec's dust extraction vacuums offer strong 130 CFM air flow and an automatic filter cleaning system to maximize vacuum power and dust collection. The "Power Take-off" outlet activates the ON/OFF mode from the tool switch, making these vacuums ideal for use with power tools. Manual ON/OFF is necessary for pneumatic tools.

- Ideal for use with power tools
- 99.93% filtration efficiency of particles 3.0 microns is standard. HEPA filters are optional.
- Can also be used as a regular wet/dry vacuum



Stepped adapter and 15' hose included as standard equipment with CS 1225 and CS 1500

Vacuum Specifications

	CS 1225	CS 1500
Power	11 Amp	11 Amp
Air flow	130 CFM	130 CFM
Tank capacity	6.6 gal.	13 gal.
Weight	24.3 lbs.	35.2 lbs.

We make no claim that use of a vacuum will eliminate contaminants. Wear an approved respirator mask and follow all appropriate OSHA safety regulations for proper ventilation, dust handling, eye protection, etc. when using a dust extraction grinder and vacuum.