

Never has changing a grinding disc been so quick and efficient

Thanks to the new **EASY-LOCK clamping nut**, abrasives can now be changed in seconds without any tools. The EASY-LOCK clamping nut will work with any abrasive with a hemp or ABS backing plate and a 7/8" arbor. That means you can change any CS Unitec/Eisenblatter abrasive on an angle grinder in a matter of seconds using this uniquely simple solution.

The secret behind it – the **EASY-LOCK self-clamping nut**
P/N 65008-1 (5/8"-11 UNC)



The clamping collar shaped on the top of the EASY-LOCK clamping nut can secure flap discs and abrasives with a "thicker" backing disc as well as centering them. "Thin" abrasives such as cutting discs, etc. can simply be secured using the reverse of the EASY-LOCK clamping nut.



1. Secure the disc loosely by hand using the EASY-LOCK clamping nut.
2. Press the spindle lock and tighten the disc by turning it clockwise by hand. That's all there is to it!
3. To release the disc, press the spindle lock and turn the disc counter-clockwise by hand.

Angle Grinders, Sanders & Polishers

Electric and pneumatic

CS Unitec offers a variety of angle grinders, sanders and polishers to satisfy your most demanding needs. High torque output, variable speed and powerful motors make them ideal for use in metal fabrication, construction, shipyards, refineries, power plants and other heavy industries. Integrated dust extraction guard and vacuum systems are available for some models.

Pneumatic Angle Grinder, 4-1/2" and 5"

1 HP mini grinder with 5/8" spindle

The L 1509 AIR is a powerful, lightweight pneumatic angle grinder for grinding, cleaning, deburring, blending and smoothing. This lightweight, versatile angle grinder is ideal for use in the most demanding grinding and sanding applications.



L 1509 AIR
(6500 RPM)

L 1509 AIR Specifications

Power	1 HP
Speed	6500 RPM
Max. diameter	5"
Air consumption	33 CFM @ 90 PSI
Air connection	1/4"
Weight	4.25 lbs.

- Heavy-duty pneumatic motor (1 HP / 6500 RPM) stands up to continuous use
- Accepts both 4-1/2" and 5" grinding discs
- Spindle size: 5/8"-11 UNC
- Removable side handle can be mounted on either side of the tool
- Spindle lock