

HB 4400 for Subsea Drilling



Hydraulic for marine and construction – works underwater

Safe • Reliable





- Ideal for industrial, construction, marine and mining applications
- Drill structural steel and other metals
- Hydraulic motor safe for underwater use
- Manually operated permanent magnet with ratchet control has holding strength of 1300 lbs.

Drill up to 2-1/16" dia.

- Uses annular cutters
- Twist drilling up to 1/2" dia.
- Automatic lubrication



With a 3/4" chuck (Part No. 602045A), this model easily converts to a standard drill press with a 3" stroke.

Cutter Capacity	Twist Drill / Countersink	Stroke (length)	Speed Range (RPM)
			
Ø 2 1/16"	1/2"	Up to 3 3/4"	0-630

Model HB 4400
Hoses not included



Model HB 4400 Specifications

Motor Power (Hydraulic)	1.5 HP
Weight	48 1/2 lbs.
Hole Capacity	2 1/16" dia.
Twist Drill Capacity	1/2" dia.
No Load Speed, Variable	0-630 RPM
Hydraulic Supply	Flow 6.5 GPM @ 2000 PSI
Magnet Base Size	7 1/4" W x 3" L
Dimensions	18 1/2" H x 12 1/2" L x 7" W
Magnetic Force (1" plate)	1300 lbs.
Automatic Lubrication	Included

► *Annular Cutters: pages 34-41* ► *Accessories: pages 42-50*