

ECO-32T and ECO-32TAK



Reversible motor for drilling and tapping applications



Model ECO-32T

- Strong 9.5 Amp double-insulated reversible motor
- Stepless variable-speed control, 100-450 RPM
- Compact height of 14¹/₄" allows drilling in tight spaces
- Lightweight and portable at only 24 lbs.
- Best power-to-weight ratio in the industry
- HD dual-coil magnet has holding strength of 3080 lbs.
- Drills up to 1¹/₄" diameter holes with Annular Cutters and taps up to ³/₄"
- Optional Power Assist to maintain maximum RPM under full load (*Part No. 020.0330*)

See page 21 for more information.



With a ¹/₂" chuck (*Part No. IBK-17*), these models easily convert to standard drill presses with a 7¹/₂" stroke for conventional twist drills.



Standard equipment includes carrying case, tap collet set, safety chain, carabin hook and allen keys.



Tap collet set included

Includes one-year warranty



Model ECO-32TAK has an automatic cooling/lubrication system built into the arbor.



Model ECO-32T and ECO-32TAK

Motor Power	9.5 Amp / 110 Volt*
Weight	24 lbs.
Hole Capacity	1 ¹ / ₄ " dia.
Twist Drill Capacity	¹ / ₂ " dia.
Tapping Capacity	³ / ₁₆ "- ³ / ₄ " dia.
Speeds	100-450 RPM
Magnet Base Size	6 ⁵ / ₁₆ " L x 3 ¹ / ₄ " W
Dimensions	14 ¹ / ₄ " H x 9 ¹ / ₂ " L x 4 ³ / ₈ " W
Magnetic Force (1" plate)	3080 lbs.
Arbor Bore	³ / ₄ "
Manual Lubrication	Order Model ECO-32T
Automatic Lubrication	Order Model ECO-32TAK

* 220 Volt / 50 Hz also available ** Power Assist Part No. 020.0330



Cutter capacity up to 1¹/₄" dia., stroke: 5³/₄"

Twist drill capacity up to ¹/₂" dia., stroke: 7¹/₂"

Tapping capacity up to ³/₄" dia.

See pages 18-24 for Annular Cutters and Accessories.