

Pneumatic and Electric Nibblers

Easily cut sheet metal and steel up to 3/8" thick

- Pneumatic or electric power is ideal for cutting sheet metal, steel plate, weldments and double sheets, as well as exotic materials and plastics
- Two-speed gearbox (model CS-3400-P or -E)
- Heavy-duty construction
- Head can be rotated to four 90° positions (on selected models)
- Cut over 90° bends with optional die
- Maximum cutting capacity:
Mild Steel: up to .375"
Stainless Steel: up to .195"
Aluminum: up to .500"
- Ideal for use in underground storage tank removal, I-beam splitting, plate cutting and more
- Lightweight construction with quick-change punch and die



CS-3400 cuts up to 3/8" thick steel.



Model No.	Power	CFM	Working Speed (ft./min.)	Start Hole Dia.	Min. Radius	Strokes per Minute	Max. Sheet Thickness			Weight (lbs.)
							Mild Steel	Stainless Steel	Aluminum	
<i>Electric (110 Volt)</i>										
<i>CS-350-E</i>	12 Amp	–	4	1.25"	.280"	650	.135"	.090"	.135"	7.5
<i>CS-500-E</i>	12 Amp	–	4.5	1.25"	3.125"	600	.197"	.135"	.276"	8.5
<i>CS-700-E</i>	17.4 Amp	–	5	2.75"	5.5"	400	.276"	.197"	.394"	26
<i>CS-3400-E*</i>	17.4 Amp	–	5.2	3"	16"	230 / 370	.375"	.276"	.500"	32
<i>Pneumatic</i>										
<i>CS-350-P</i>	1.5 HP/90 PSI	54	4	1.25"	.280"	530	.135"	.090"	.135"	10
<i>CS-500-P</i>	1.5 HP/90 PSI	54	4.5	1.25"	3.125"	530	.197"	.135"	.276"	10.5
<i>CS-700-P</i>	4 HP/90 PSI	100	5	2.75"	5.5"	340	.276"	.197"	.394"	27
<i>CS-3400-P*</i>	4 HP/90 PSI	100	5.2	3"	16"	210 / 350	.375"	.276"	.500"	32

* 2-speed gearbox