

FINGER BELT SANDER *Variable-speed*

Ideal for angles and tight spaces, as well as pipes and curves. The swivel-mounted arm, with 140° flexibility, reaches into corners, grooves and folds.

The LBS 1105 VE finger belt sander saves time grinding in confined and difficult areas. It uses belt sizes 3/16" to 1-1/8" wide by 21" long. The sanding arm rotates up to 140° for reaching into corners, grooves and folds, including pipes and curves.

The finger sander is ideal for grinding, blending, polishing and deburring ferrous and nonferrous metal. It also works on wood, plastic, fiberglass and other material. Speed is adjustable from 13 to 39 ft./sec.



LBS 1105 VE with 3/8" sanding arm. Interchangeable 1-1/8" arm shown at right.



Finger Belt Sander Accessories

Abrasive sanding belt (10/pkg.)

Size	Grit	Part No.
3/16"	60	303 615
3/16"	120	303 623
3/8"	40	257 101
3/8"	60	257 105
3/8"	120	257 102
3/8"	220	257 103

1-1/8"	60	255 328
1-1/8"	120	255 329
1-1/8"	220	255 330

Surface conditioning fleece belt (3/pkg.)

Size	Grit	Part No.
3/8"	Medium (red)	318 663
3/8"	Fine (blue)	318 671

1-1/8"	Medium (red)	318 647
1-1/8"	Fine (blue)	318 655

SuperPolish Belt (1/pkg.)

For high-gloss polishing, without polishing agents, in two steps

Size	Grit	Part No.
1-1/8"	600	318 132
1-1/8"	1500	318 140

Optional Equipment

(1) 3/8" sanding arm (curved) – Part No. 256 532

(1) 1-1/8" sanding arm (large roller) – Part No. 258 888



Narrow filing arm and 140° adjustability allow sanding and grinding in confined and difficult areas.

Finger Belt Sander Specifications

Order Number: LBS 1105 VE

Belt speeds	13 to 39 ft./sec.
Motor	6.1 AMP
Weight	5.5 lbs.

Standard Equipment

- (1) 3/8" sanding arm (pointed) – Part No. 256 525
- (1) abrasive belt kit, grits 40/120/220 – 1 set
- (1) side handle – 194 034
- (1) hexagon socket screw key – 115 460

Standard equipment includes a metal carrying case.

