AIRBOR™ AB-4300

Motor and magnet are powered completely by compressed air

Cutter capacity 2¹/16" dia.

Pneumatic power for hazardous environments

AIRBOR

MAGNET

OFF

0

DRILL


ATEX Certified

Safe • Reliable

- Inherently safer than electromagnetic drills in hazardous atmospheres and wet environments where electricity requires "hot work permits"
- ATEX certified
- Industry's first completely air-operated magnetic drill - NO ELECTRICITY!
- Fail-safe permanent magnet is activated "on" and "off" by air pressure; in the event of a loss of air flow, the magnet will not disengage
- 1600 lbs. magnet holding strength

Drill up to 2-1/16" dia.

- Uses annular cutters up to 2-1/16" dia.
- · Twist drilling capacity up to 5/8" dia.
- Powerful 1.6 HP drill motor
- Long drill stroke up to 101/4"
- Pressurized coolant system lubricates cutter and reduces risk of sparking





AB-4300-2R shown with extra rack up (left) and extra rack down (right).

Model Comparison			
AB-4300-2R		AB-4300-2	
Drill Stroke			
w/cutters 10 ¹ /4"	w/chuck 7 ¹ /2"	w/cutters 4 ⁷ /8"	w/chuck 1 ³ /4"
Height			
closed 13 ¹ /2"	open 22"	closed 13 ¹ /2"	open 17 ¹ /2"
Weight			
43 lbs.	20 kg	38 lbs.	18 kg

Annular Cutters: pages 54-64 > Accessories: pages 65-71

UNITEC



With a geared chuck adapter (Part No. IBC 18) and extra rack (Model No. AB-4300-2R), AIRBOR™ easily converts to a standard drill press with a $7^{1}/2^{"}$ stroke.



Pressurized lubrication system (Part No. 9 4002 0020 N)







Speed Range (RPM)



Cutter Capacity

Ø 2¹/16"

T.

5/8"

Up to 10¹/4"

Model AB-4300-2 / AB-4300-2R Specifications

1.6 HP	
64 CFM (1/2" NPT Air Connection)	
2 ¹ /16" dia.	
400 RPM	
8 ³ /4" L x 3 ¹ /2" W	
13 ¹ /2" H x 12 ¹ /2" L x 4 ³ /4" W	
1600 lbs.	
³ /4" Weldon Shank	
Included	
Order Model AB-4300-2	
Order Model AB-4300-2R	



Model AB-4300-2