# AIRBOR™ AB-4300

Motor and magnet are powered completely by compressed air



# Pneumatic power for hazardous environments

### ATEX Classified

#### Safe • Reliable

· Inherently safer than electromagnetic drills in hazardous atmospheres and wet environments where electricity requires "hot work permits"

- ATEX classified
- · Industry's first completely air-operated magnetic drill - NO ELECTRICITY!
- · Fail-safe permanent magnet is activated "on" and "off" by air pressure; in the event of a loss of air flow, the magnet will not disengage
- 1600 lbs. magnet holding strength

## Drill up to 2-1/16" dia.

- Uses annular cutters up to 2-1/16" dia.
- · Twist drilling capacity up to 5/8" dia.
- · Powerful 1.6 HP drill motor
- Long drill stroke up to 10<sup>1</sup>/<sub>4</sub>"
- · Pressurized coolant system lubricates cutter and reduces risk of sparking





AB-4300-2R shown with extra rack up (left) and extra rack down (right).

#### **Model Comparison**

_ A _	10			
AB	=44.4	1111	レント	•
	70	$\mathbf{v}$		

A	B-	43	0	0	-2
---	----	----	---	---	----

Drill Stroke				
w/cutters	w/chuck	w/cutters	w/chuck 1 <sup>3</sup> /₄"	
10 74	1 12	4 78	1 -/4	
Height				
closed	open	closed	open	
13 <sup>1</sup> /2"	22"	13 <sup>1</sup> /2"	17 <sup>1</sup> /2"	
Weight				
lbs.	kg	lbs.	kg	
43	20	38	18	
	10 <sup>1</sup> / <sub>4</sub> "  closed 13 <sup>1</sup> / <sub>2</sub> "	w/cutters w/chuck 10 1/4" 7 1/2"  Heiclosed open 13 1/2" 22"  Weilbs. kg	w/cutters $7^{1}/2^{1}$ w/chuck $4^{7}/8^{1}$ $4^{7}/8^{1}$ $Height$ closed open closed $13^{1}/2^{1}$ $22^{1}$ $13^{1}/2^{1}$ $Weight$ lbs. kg lbs.	



adapter (Part No. IBC 18) and extra rack (Model No. AB-4300-2R), AIRBOR™ easily converts to a standard drill press with a 71/2" stroke.

Pressurized lubrication system (Part No. 9 4002 0020)





Speed Range





**Cutter Capacity** 

AIRBOR S

MAGNET

DRILL





(RPM) 400

Model AB-4300-2 / AB-4300-2R Specifications

Motor Power (Pneumatic)	1.6 HP		
Air Consumption @ 90 PSI	64 CFM (1/2" NPT Air Connection)		
Hole Capacity	2 <sup>1</sup> / <sub>16</sub> " dia.		
No Load Speed	400 RPM		
Magnet Base Size	8 <sup>3</sup> / <sub>4</sub> " L x 3 <sup>1</sup> / <sub>2</sub> " W		
Dimensions	$13^{1}/_{2}$ " H x $12^{1}/_{2}$ " L x $4^{3}/_{4}$ " W		
Magnetic Force (1" plate)	1600 lbs.		
Arbor Bore	3/4" Weldon Shank		
Automatic Lubrication	Included		
Stroke Length 47/8"	Order Model AB-4300-2		
Stroke Length 10 <sup>1</sup> / <sub>4</sub> "	Order Model AB-4300-2R		

➤ Annular Cutters: pages 36-46 ➤ Accessories: pages 47-53

