

# CSU 50RLAC

## Lightweight, two-speed, high-performance drills



Cutter capacity  
2" dia.

### Powerful • Reliable

- Strong 10.5 Amp motor
- Compact, lightweight and portable – 16-1/2" high, 29 lbs.
- 2-gear variable speed gearbox
- Designed for continuous use

### Drill up to 2" dia.

- Uses annular cutters up to 2" dia.; 5-1/4" stroke
- Twist drilling capacity up to 7/8" dia.
- Tapping capacity up to 15/16" dia.\*
- Automatic lubrication system

### Keyless Cutter Mount

- Optional "twist and lock" keyless arbor
- Also includes manual arbor for 3/4" Weldon shank (MT2) with set screws



### Integrated Safety

- SafeMag™ Green/Red LED magnetic force indicator for safe operation
- Equipped with CoolMag™ overheat protection
- Emergency-off function



With optional geared chuck, these models easily convert to standard drill presses with a 4 1/2" stroke for conventional twist drills. Optional 3/4" geared chuck available (Part No. IBC 22).

### REVERSIBLE

**Model CSU 50RL** has a variable-speed, reversible motor for tapping up to 15/16"

Optional quick-change tapping chuck with MT2 connection (Model GSW-222) has flexible collet to fit taps 5/16" to 5/8"



### CSU 50RLAC Specifications

Motor Power	10.5 Amp / 110 Volt
Weight	29 lbs.
Hole Capacity	2" dia.
Twist Drill Capacity	7/8" dia.
Tapping Capacity	15/16"
Speeds	1: 250 RPM, 2: 450 RPM
Magnet Base Size	6 1/2" L x 3 1/2" W
Dimensions	16 1/2" H x 9" L x 6 3/8" W
Magnetic Force (1" plate)	3750 lbs.
Arbor Bore	3/4" Weldon Shank
Spindle	MT2
Automatic Lubrication	Included

**Standard Equipment** includes auto lubrication, manual chuck with set screws, safety chain, carabin hook, allen keys, and carrying case.

➤ **Annular Cutters:** pages 36-46 ➤ **Accessories:** pages 47-53