

# **MABasic 450**



## Professional-grade, two-speed versatility

#### Powerful • Reliable

- 10.5 Amp double-insulated motor
- MT2 3/4" direct arbor with automatic cooling

#### Drill up to 1-3/4" dia.

- Uses annular cutters up to 1-3/4" dia.
- Twist drilling capacity up to 3/4" dia.
- Internal lubrication system
- Compact and lightweight





With included 1/2" geared chuck, the MABasic 450 easily converts to standard drill press for conventional twist drills. Optional 3/4" geared chuck available (Part No. IBC 22).

Equipped with Electronic Safety Shutoff Sensor (see p. 3)

### MABasic 450 Specifications


Motor Power	10.5 Amp / 110 Volt
Weight	29 lbs.
Hole Capacity	1 <sup>3</sup> / <sub>4</sub> " dia.
Twist Drill Capacity	3/4" dia.
Speeds	250 / 450 RPM (2 gears)
Magnet Base Size	6 <sup>5</sup> /8" L x 3 <sup>1</sup> /3" W
Dimensions	17" H x 9 <sup>1</sup> / <sub>2</sub> " L x 6 <sup>1</sup> / <sub>2</sub> " W
Magnetic Force (1" plate)	3080 lbs.
Arbor Bore	3/4" Weldon Shank
Spindle	MT2
Internal Lubrication	Oil Bottle Included



## Standard Equipment includes Juhrication hottl

includes lubrication bottle, 1/2" geared chuck\*, safety strap, carabin hook, allen keys, pilot pin and carrying case.

<sup>\*</sup> Optional 3/4" geared chuck available



➤ Annular Cutters: pages 36-46 ➤ Accessories: pages 47-53