



Cutter capacity
4" dia.

Model 2 1345 0010 – Hydraulic

Ideal for use in Ex Zones and subsea applications

ATEX Classified

Safe • Reliable

- Hydraulic motor safe for underwater use
- Ideal for industrial, construction, marine and mining applications
- ATEX Classified EX II 2Gc IIB T5
- Drill structural steel and other metals
- Manually operated permanent magnet with lever control has holding strength of 1874 lbs.

Drill up to 4" dia.

- Uses annular cutters up to 4" dia.
- Twist drilling capacity up to 1-1/4" dia.
- Tapping capacity up to 1" dia.



Model 2 1345 0010 Specifications

Motor Power (Hydraulic)	3.4 HP
Weight	50 lbs.
Hole Capacity	4" dia.
Twist Drill Capacity	1 1/4" dia.
No Load Speed, Variable	40-250 RPM
Hydraulic Supply	Flow 5.3 GPM @ 2000 PSI
Magnet Base Size	11 11/16" L x 4" W
Dimensions	21 1/2" H x 15 7/16" L x 7 3/4" W
Magnetic Force (3/8" plate)	1874 lbs.
Spindle	MT3

Pipe Clamp – Model 2 1330 8500



Optional clamp allows right angle drilling of steel, cast iron, cement and plastic pipes up to 19-1/2" dia.

Extension chains available for pipes up to 43-1/4" dia.
 P/N 5 1201 9030* – For pipes up to 31-1/2" (800mm)
 P/N 5 1201 9020* – For pipes up to 43-1/4" (1100mm)
 * 2 pieces needed for one clamp

Cutter Capacity	Twist Drill / Countersink	Ream / Tap	Stroke (length)	Variable Speed (RPM)	Reversible (CW/CCW)
ø 4"	ø 1 1/4" / ø 2"	ø 1 1/8" / ø 1"	12"	40-250	

Standard Equipment includes hydraulic hose set, coolant bottle, arbor adapter to 3/4" Weldon, arbor adapter to 1-1/4" Weldon, safety chain, drift key, allen keys and carrying case.

➤ *Annular Cutters: pages 36-46* ➤ *Accessories: pages 47-53*