

Nut Runners - High Torque

ATEX

PNEUMATIC AND HYDRAULIC NUT RUNNERS

Pneumatic and hydraulic: ideal for turning valves, tightening, tapping, reaming, pipe beveling, expanding and more



- Worm gear drive provides high torque – up to 554 ft.-lbs.
- Lightweight and reversible
- Compact angle head allows access to confined spaces



Model
6 1055 0075

Model numbers pictured above (listed from top to bottom): 6 1055 0075 (with male drive), 6 1055 0010 (female), 6 1014 0075 (with male drive)

Available with Male or Female Square Drives, in a variety of sizes



Male Sq. Drive Head
1/2" or 3/4"



Female Sq. Drive Head
3/4" or 7/8"

Square Drive Accessories



6 1015 7030 – 3/4" Male Square Drive with retaining hole (included with model numbers 6 1014 0075, 6 1055 0075 and 6 1056 0075)

6 1017 7940 – 3/4" Male Square Drive with retaining pin



3 6339 4910 – 1/2" Male Square Drive with retaining hole (included with model numbers 6 1014 0099, 6 1055 0099 and 6 1056 0099)



6 1018 7940 – 1/2" Male Square Drive with retaining pin



6 1016 7940 – 1" Male Square Drive

| Pneumatic Nut Runner Model No. | Square Drive F=Female M=Male | Stall Torque at 90 PSI (ft.-lbs.) | Free Speed (RPM) | Load Speed (RPM) | Power (HP) | CFM at 90 PSI | Side to Center Distance (inches) | Length (inches) | Weight (lbs.) | Air Conn-ec-tion (inches) | Hose ID (inches) |
|--------------------------------|------------------------------------|-----------------------------------|------------------|------------------|------------|---------------|----------------------------------|-----------------|---------------|---------------------------|------------------|
| 6 1014 0075* | 3/4" M | 95 | 200 | 100 | 0.9 | 46 | 1 | 22 | 11 | NPT 3/8 | 1/2 |
| 6 1014 0099 | 1/2" M | 95 | 200 | 100 | 0.9 | 46 | 1 | 22 | 11 | NPT 3/8 | 1/2 |
| 6 1055 0075* | 3/4" M | 405 | 40 | 22 | 0.9 | 46 | 1 | 21 | 10 | NPT 3/8 | 1/2 |
| 6 1055 0099 | 1/2" M | 405 | 40 | 22 | 0.9 | 46 | 1 | 21 | 10 | NPT 3/8 | 1/2 |
| 6 1056 0075* | 3/4" M | 133 | 120 | 67 | 0.9 | 46 | 1 | 21 | 11 | NPT 3/8 | 1/2 |
| 6 1056 0099 | 1/2" M | 133 | 120 | 67 | 0.9 | 46 | 1 | 21 | 11 | NPT 3/8 | 1/2 |
| 6 1057 0075* | 3/4" M | 73.5 | 250 | 125 | 0.9 | 46 | 1 | 21 | 11 | NPT 3/8 | 1/2 |
| 6 1057 0099 | 1/2" M | 73.5 | 250 | 125 | 0.9 | 46 | 1 | 21 | 11 | NPT 3/8 | 1/2 |
| 6 1061 0010 | 7/8" F | 405 | 40 | 22 | 0.9 | 46 | 1 | 21 | 11 | NPT 3/8 | 1/2 |

* Also available with 3/4" Female Square Drive – use 0010 instead of 0075 in model number.

| Hydraulic Nut Runner Model No. | Square Drive F=Female M=Male | Drive Torque | Free Speed (RPM) | Load Speed (RPM) | Power (HP) | Oil Flow (GPM) | Oil Pressure (PSI) | Side to Center Distance (inches) | Length (inches) | Weight (lbs.) | Conn-ec-tion Quick Couplers |
|--------------------------------|------------------------------------|--------------|------------------|------------------|------------|----------------|--------------------|----------------------------------|-----------------|---------------|-----------------------------|
| 3 6242 0010* | 3/4" F | 369 | 40 | 22 | 1.6 | 4 - 13 | 90-2000 | 1 | 20 | 22 | 1/2" FF |
| 3 6243 0010* | 3/4" F | 125 | 180 | 90 | 1.6 | 4 - 13 | 1300-2000 | 1 | 20 | 22 | 1/2" FF |

* Also available with 1/2" (3 6242 0099) and 3/4" (3 6242 0075) Male Square Drive