

Pneumatic Drills and Drive Units

High-torque reversible drilling and tapping machines



- High-torque reversible drilling, tapping and threading machines
- Ideal for drilling, reaming, tube rolling, tube expanding and tapping
- Use for special applications including mills, spindles, slides, controllers, pipe tapping, valve turning and more
- Drill chucks and Morse Taper arbors
- Hammer drills for drilling concrete with up to 2200 blows per minute
- Special OEM air motors available on request
- 6-month warranty

D-handle Drills



Model 2 1310 0010

Morse Taper Drills w/ Feed Spindle



Model 2 2089 0030 with reverse and safety twist throttle



See page 64 for Rotary Hammer Drills

Pneumatic Hammer Drills



Model 2 1266 0010

Pneumatic Pistol Drills



Model 2 1261 0010

Model No.	Motor Power (HP)	Load Speed (RPM)	Reversible	Chuck/ Arbor	Drilling Cap. in Steel	Tube Rolling Cap.	Torque Output (ft./lbs)	CFM at 90 PSI	Length	Feed Length	Weight (lbs.)
Pistol Drills											
2 1261 0010	0.7	850	NO	1/2" Chuck	1/2"	N/A	7 max.	21	9 3/4"	N/A	4.6
Hammer Drills (for concrete and underwater applications)											
2 1266 0010	0.75	950	NO	1/2" Chuck	1/2"	N/A	7 max.	21	12"	N/A	6.7
D-handle Drills											
2 1310 0010	0.8	650	NO	1/2" Chuck	1/2"	N/A	8 max.	24	12 1/2"	N/A	12
2 1311 0010	0.8	650	NO	MT1	5/8"	N/A	8 max.	24	11"	N/A	12
Morse Taper Drills w/ Feed Spindle											
2 2089*	1.7	250	YES	MT3	1 1/4"	1"	36 max.	24	26 1/2"	1 5/8"	28
2 2506*	2.5	220	YES	MT3	1 1/4"	2"	63 max.	70	26 1/2"	2 1/2"	32
2 2502*	2.5	80	YES	MT4	2"	2 1/2"	173 max.	70	26 1/2"	2 1/2"	37

* The last four digits of the Model No. identify the type of throttle. Please specify the four digits when ordering: 0010 for Lever Throttle or 0030 for Safety Twist Throttle.