

CSU 80AC & CSU 100/3RL



CSU 80AC

Powerful high-torque motor with multiple speeds



With a 3/4" chuck (Part No. IBC 21) or MT3, this model easily converts to a standard drill press with a stroke of 6 1/2".

CSU 100/3RL

Powerful reversible motor for drilling and tapping



Optional MT3 tapping chuck with two variable clamp collets (Model GSW-830C) fits taps 3/8" to 1-1/8"

CSU 80AC Specifications

Motor Power	15 Amp / 110 Volt*
Weight	57 lbs.
Hole Capacity	3 ³ / ₁₆ " dia.
Twist Drill Capacity	1 1/4" dia.
Speeds	1: 100 RPM, 2: 175 RPM 3: 245 RPM, 4: 385 RPM
Magnet Base Size	9" W x 4 ³ / ₈ " H
Dimensions	19 1/2" H x 13 ³ / ₈ " L x 7 1/2" W
Magnetic Force (1" plate)	7040 lbs.
Arbor Bore	3/4" (1 1/4" also available)
Spindle	MT3
Automatic Lubrication	Included
Power Assist	Order Accessory ZPA 402

* 220 Volt / 50 Hz also available

CSU 100/3RL Specifications

Motor Power	16 Amp / 110 Volt*
Weight	57 lbs.
Hole Capacity	4" dia.
Twist Drill Capacity	1 1/4" dia.
Tapping Capacity	1 1/8" dia.
Speeds (variable)	40-140 RPM, 120-480 RPM
Magnet Base Size	9" W x 4" H
Dimensions	19 1/2" H x 13 ³ / ₈ " L x 7 1/2" W
Magnetic Force (1" plate)	6600 lbs.
Arbor Bore	3/4" (1 1/4" also available)
Spindle	MT3
Automatic Lubrication	Included
Power Assist	Order Accessory ZPA 402

* 220 Volt / 50 Hz also available

Standard Equipment includes auto lubrication, auto chuck cutter holder, safety chain, carabin hook, allen keys, pilot pins and carrying case[†].

[†] Steel case intended mainly for shipping purposes; damage may occur in transit.

➤ **Annular Cutters:** pages 34-41 ➤ **Accessories:** pages 42-50

PORTABLE MAGNETIC DRILLS