



Cutter capacity
1 1/4" dia.

CSU 32AC & CSU 32RL



Best power-to-weight performance in the industry

Powerful • Reliable

- Strong 8.2 Amp motor
- Compact, lightweight and portable – 14-1/4" high, 24 lbs.
- Designed for continuous use
- Model CSU 32RL variable speed

Drill up to 1-1/4" dia.

- Uses annular cutters; 5-3/4" stroke
- Twist drilling up to 1/2" dia.; 7-1/2" stroke with chuck
- Tapping up to 3/4" dia.*
- Automatic lubrication system

REVERSIBLE

Model CSU 32RL
has a variable-speed
(100-450 RPM),
reversible motor for
tapping up to 3/4"



Standard Equipment includes auto lubrication, auto chuck cutter holder, safety chain, carabin hook, allen keys and carrying case. (CSU 32AC shown)



Integrated Safety

- SafeMag™ Green/Red LED magnetic force indicator for safe operation
- Equipped with CoolMag™ overheat protection
- Emergency-off function



With optional 1/2" chuck (Part No. IBC 17), these models easily convert to standard drill presses with a 6 1/2" stroke for conventional twist drills.

CSU 32AC Specifications

Motor Power	8.2 Amp / 110 Volt
Weight	24 lbs.
Hole Capacity	1 1/4" dia.
Twist Drill Capacity	1/2" dia.
Tapping Capacity	3/4" (CSU 32RL only)
Speed	450 RPM
Magnet Base Size	6 5/16" W x 3 1/4" H
Dimensions	14 1/4" H x 9 1/2" L x 4 3/8" W
Magnetic Force (1" plate)	3080 lbs.
Arbor Bore	3/4"
Spindle	1/2"-20 UNF Thread
Automatic Lubrication	Included
Reversible Motor	Order CSU 32RL
Power Assist	Order Accessory ZPA 401

* Model CSU 32RL for tapping up to 3/4" dia.