

ESD 162 Dry Core Drill

NEW Powerful Innovation in Drilling Reinforced Concrete!

- IHT soft impact technology provides faster drilling, reduced heat, extended bit life, & excellent dust extraction.



- Dry drilling up to 8" in brick/ block, 6-3/8" in reinforced concrete.
- New technology to replace the need for water in reinforced concrete; no slurry!
- Can be used for hand or rig-guided drilling .
- Dust extraction system for increased user safety.

Ergonomic design & anti-vibration handles



The ESD 162 comes with the EDMC Pro digital motor control with a service and overload indicator, soft start, & over current cut-off.

Kits Available:

Anchor Stand Kit: Part No. ESD 162 PSA
Vacuum Stand Kit: Part No. ESD 162 PSV



Specifications

Motor Power	19.5 Amp, 110 V
Load Speeds (RPM)	0-1000 RPM
Drilling Diameter	6-3/8" / 8"
Spindle Connection	1-1/4" x 7 UNC 5/8" x 11 UNC
Collar Diameter	60 mm
Weight	15 lbs (motor only)

ESD 162 Accessories

Core Bits are a Truly Unique Product, Specially Designed for the ESD 162

- Optimal results in rebar reinforced concrete, brick, block, & more.
- Maintain high working speeds during extended drilling periods.
- Highly durable diamond segments.
- Extremely cool cutting.
- Superior dust collection.



Centering Rod for starting the holes free hand - part no. 36394000



Use with CS 1445 H HEPA Vacuum

*ESD 162 & BST 162 H Stand Kit:
Part # ESD 162 POSA*

Part No.	Diameter
PB1341334	1-3/4"
PB2001334	2"
PB2121334	2-1/2"
PB3001334	3"
PB3121334	3-1/2"
PB4001334	4"
PB4121334	4-1/2"
PB5001334	5"
PB6001334	6"
PB6381334	6-3/8"
PB7001334	7"
PB8001334	8"

Distributed By:



22 Harbor Ave, Norwalk, CT 06850
4330 Center St, Deer Park, TX 77536
Phone 800-700-5919 • 203-853-9522
info@csunitec.com • www.csunitec.com