

Dust Collection Vacuums with HEPA Filtration

CS Unitec's dust extraction vacuums offer strong 130 CFM air flow and an electromagnetic pulse filter cleaning system to maximize vacuum power and dust collection.

- Ideal for use with power tools
- 99.999% HEPA filtration efficiency of particles down to 0.3 microns; automatic filter cleaning
- "Power Take Off" outlet activates the vacuum ON/OFF from the power tool switch
- Non-HEPA models available, 99.930% filtration efficiency
- Kit available to connect two power tools (P/N 198804)



Model CS 1445 H automatically "pulse" cleans filters without interrupting operation!



CS 1225 H

HEPA Vacuum Specifications

| | CS 1225 H | CS 1500 H | CS 1445 H |
|-------------------|-----------|-----------|-----------|
| Power | 11 Amp | 11 Amp | 11 Amp |
| Air flow | 130 CFM | 130 CFM | 130 CFM |
| Tank capacity | 6.6 gal. | 13 gal. | 9 gal. |
| Weight | 24.3 lbs. | 35.2 lbs. | 24.3 lbs. |
| Filter P/N (2pk.) | 428956 | 428956 | 428956 |

Standard Vacuum Specifications

| | CS 1225 | CS 1500 | CS 1445 |
|-------------------|-----------|-----------|-----------|
| Power | 11 Amp | 11 Amp | 11 Amp |
| Air flow | 130 CFM | 130 CFM | 130 CFM |
| Tank capacity | 6.6 gal. | 13 gal. | 9 gal. |
| Weight | 24.3 lbs. | 35.2 lbs. | 24.3 lbs. |
| Filter P/N (2pk.) | 416069 | 416069 | 416069 |

Activate vacuum on/off from power tool controls



CS 1500

Optional Filter Bags

Paper filter bags for CS 1225 and CS 1445 - P/N 416014 (5-pack)

Plastic filter bags for CS 1225, CS 1445 and CS 1500 - P/N 421742 (5-pack)

Paper filter bags for CS 1500 - P/N 416021 (5-pack)

Slurry filter bags for CS 1500 - P/N 420592 (3-pack)

We make no claim that use of a vacuum will eliminate contaminants. Wear an approved respirator mask and follow all appropriate OSHA safety regulations for proper ventilation, dust handling, eye protection, etc. when using a dust extraction grinder and vacuum.

Air-Powered Dust Collection Vacuum – KAV 30 AIR

**Collection of dry dust/debris and non-flammable liquids
ATEX classified; antistatic vacuum and air-supply hose**



- Antistatic vacuum and air supply hose
- ATEX classified Ex II 2 GcT6 for use in Gas Zone 2 and Dust Zone 22
- Robust stainless steel construction
- Floor tool kit for general cleaning work
- Double filtration with optional 14" Permaflow filter
- Optional HEPA filter – for collection of hazardous dust
- Disposable paper filter or reusable cloth bag for wet use

KAV 30 AIR Vacuum Specifications

| | Dry Model 303.10KAV30/D | Wet/Dry Model 303.10KAV30/WD |
|--------------------------|----------------------------|---------------------------------|
| CFM @ 90 PSI | 35 | 35 |
| Output flow | 70 CFM | 70 CFM |
| Tank capacity | 6.8 gal. | 6.8 gal. |
| Weight | 32 lbs. | 32 lbs. |
| Paper Filter P/N (10pk.) | 303.1030 | 303.1030 |
| HEPA Filter P/N | 303.1060 | 303.1060 |