MEGA HIPPO Mixing System



Industry Standard System for Self-Levelers!

NEW 20 AMP MOTOR: MAINTAIN HIGHER SPEEDS!

Now handle a wider range of materials – mix thicker compounds and heavier aggregate

New 3-speed motor with 33% more power Higher torque for use with even more materials,

including thicker compounds and heavier aggregate





Large batch capacity Thoroughly mix batches up to 6 bags (23 gallons/350 lbs.) of self-levelers

Reduced dust and splatter

Replaceable liners Increase productivity and eliminate cross-contamination

Balanced tilting cradle For easy, smooth pouring

Slim profile & compact height Easily maneuver through doorways and transport between jobsites, even in enclosed trucks and vans



Self-Leveling Over/Underlayments • Engineered Concrete • Cement Screeds Sealants • Adhesives • Resins • Epoxies • Textured Coatings • Slurries • and more

Cost Savings Example when using the HIPPO Mixing System:

Reduce labor costs by up to 86%

XIMATS

Increase output by up to 11x!

1-800-700-5919



UNITEC

A flexible solution for selfleveling jobs of all sizes!

Configure your ideal HIPPO System to maximize profit, increase output and boost your bottom line.



PMH80F-DC3.1 Ideal for flat floors. Allows accurate placement - pour and spread at the same time. 4 casters.
PMH80X-DC3.1 Ideal for rough terrain. Increased height - pour directly into buckets or carts. 2 tires/2 legs.
PMP80 Pelican cart and canister. Ideal for transporting and pouring materials and mixing back-to-back batches.

MEGA HIPPO Mixing System



PORTAMIX® MEGA HIPPO

Capacity	6 Bags
Output	Up to 2200 lbs./hour
Speeds	175/300/430
Weight	109 lbs.
Paddles	2 included

Standard equipment included: Standard

Equipment includes: mixing motor (PH 2516 R), bucket, removable liner (PH705), canister cover with hinged lid (PH718) and 2 paddles – TW225 for half batches (2-3 bags) and TW225D for full batches (4-6 bags)



Replaceable Liners improve productivity, reduce cleanup, and eliminate cross-contamination







