

SPECIAL OFFER

UNITEC
Official Trelawny Importers to the USA

TRELAWNY
SURFACE PREPARATION TECHNOLOGY™

ANY LOW-VIBRATION VL NEEDLE OR CHISEL SCALER PURCHASED BY 4/30/2020 WILL COME COMPLETE WITH A FREE SERVICE KIT WORTH \$125.63*

*Price stated applies to kit for the VL303

VL203 & VL223



- 199.2003 SK VL203 Needle Scaler
- 199.2303 SK VL203 Needle Scaler with vacuum shroud
- 199.2105 SK VL203 Needle/Chisel Kit
- 199.2203 SK VL203 Chisel Scaler



- 199.2103 SK VL223 Needle Scaler
- 199.2313 SK VL223 Needle Scaler with vacuum shroud
- 199.2113 SK VL223 Needle/Chisel Kit
- 199.2213 SK VL223 Chisel Scaler

Corresponding Service Kits:

- 446.2003 VL2 Needle Scalers
- 446.2203 VL2 Chisel Scalers

VL303



- 199.3003 SK VL303 Needle Scaler
- 199.3005 SK VL303 Needle Scaler with vacuum shroud
- 199.3103 SK VL303 Needle/Chisel Kit
- 199.3203 SK VL303 Chisel Scaler

Corresponding Service Kits:

- 446.3003 VL3 Needle Scalers
- 446.3303 VL3 Chisel Scalers

ATEX OPTIONS



- 139.2403 SK VL203Ex Needle Scaler
- 139.2423 SK VL223Ex Needle Scaler with vacuum shroud
- 139.2433 SK VL303Ex Needle Scaler

Corresponding Service Kits:

- 446.2003X VL2ex Needle Scalers
- 446.3003X VL3ex Needle Scalers

Working in a potentially explosive environment? Ask us about our ATEX certified models.

Removing hazardous coatings such as Lead or Asbestos? Ask about integrated TVS dust shrouds and HEPA vacuums.

Working at height? Drop Protection kits available to safely tether tools.

JUST USE THE SK PART NUMBER TO RECEIVE YOUR FREE SERVICE KIT WITH ANY PURCHASE OF A LOW-VIBRATION VL NEEDLE OR CHISEL SCALER.

HAND-ARM VIBRATION EXPOSURE CALCULATOR

Tool or process name	Vibration magnitude m/s ²	Exposure points per hour	Time to reach EAV 2.5 m/s ² A (8)		Time to reach ELV 5 m/s ² A (8)	
			Hours	Minutes	Hours	Minutes
Trelawny VL303 Needle Scaler	2.3	11	9	27	>24	
Competitor Brand Needle Scaler	17.5	613		10		39

HANDS UP IF YOU NEED VIBRO-LO™



Did you know over 10 million workers are at risk of serious vibration related injury from using old fashioned high vibrating power and hand tools?



Developed to combat the damaging effects of hand arm vibration on both the short and long term health of operators Trelawny's Vibro-Lo™ Needle and Chisel scalers offer the safest levels of working vibration in the market.

Both the ANSI standard and the European Union standard set a maximum daily exposure of 5 meters per second squared of vibration acceleration for an 8-hour time-weighted average, and they require monitoring and controls above 2.5 meters/second squared for an 8-hour time-weighted average.

Trelawny's Vibro-Lo™ needle scalers allow over a full 8 hour shift before reaching the Exposure Action Value compared to just 10 minutes of competitor products.

Not only do the tools protect operators from injury, the added comfort in operation leads to increased productivity.

By engineering tools to meet such stringent standards Trelawny tools benefit from greater efficiency, reduced air consumption and fewer breakdowns compared to competitor products.

In order to keep Trelawny tools running at their best Trelawny supply comprehensive service kits extending the operating life of the tool to over 300 working hours* without costly downtime on site.

Designed to be maintained without the use of specialist tools, they can be maintained on the jobsite for maximum working time. Integrated QR codes on the serial plate take operatives straight to a simple service and maintenance guide allowing them to keep on working while other tools are in the repair shop.



Take the Vibro-Lo™ challenge and contact us now to arrange your Free Trelawny VL needle scaler demonstration.



*Consumable life dependent on application.
For further guidance see:
<https://www.hse.gov.uk/vibration/hav/vibrationcalc.htm>