AutoMAB 450



Powerful • Reliable

- 10.5 Amp double-insulated motor
- Designed for continuous use
- Lightweight, 33 lbs.
- · Automatic feed with auto stop and retraction
- Power feed automatically controls drill pressure to maintain optimal RPM and feed rate

Drill up to 2" dia.*

- Uses annular cutters up to 2" dia. (*with TCT Carbide cutters, 1-3/4" dia. with all other annular cutters)
- Twist drilling capacity up to 3/4" dia.
- 6" stroke, 3-1/3" stroke with chuck
- Integrated cutting oil reservoir
- Automatic internal lubrication

Integrated Safety

• Simple, ergonomic arrangement of controls for one-handed operation



JNITEC

vered by

BDS

Mode	I AutoMAB 4	450 Snec	ifications
NOGC			


Motor Power	10.5 Amp / 110 Volt		
Weight	35 ¹ /4 lbs.		
Hole Capacity	2" dia.*		
Drilling Depth	2-3/8" with pilot pin 4-3/8" without pilot pin		
Speed	250 / 450 RPM (2 gears)		
Magnet Base Size	6 ⁵ /8" L x 3 ¹ /3" W		
Dimensions	16 ⁷ /8" H x 9 ¹ /8" L x 7 ³ /4" W		
Magnetic Force (1" plate)	3750 lbs.		
Arbor Bore	³ /4" Weldon Shank		
Automatic Lubrication	Included		
Spindle	MT2		

Standard Equipment includes auto lubrication, safety strap, carabin hook, MT2 drift key, allen keys and steel carrying case.[†]

•

[†] Steel case intended mainly for shipping purposes; damage may occur in transit.

* 2" dia. with TCT Annular Cutters; 1-3/4" capacity with all other annular cutters



Annular Cutters: pages 54-64 > Accessories: pages 65-71



1-800-700-5919