PORTABLE **PIPE DRILLING** SOLUTION

PipeMAB 200

PipeMAB 525

The new PipeMAB magnetic drilling machines from CS Unitec permanent magnets allows Made in Germany. The patented pipe magnetic clamping system with two permanent magnets automatically adapts to the pipe as well as inside and outside diameter.

The swivel arrangement of the pivoting to conform to any 3 inch (85 mm) pipe diameter or larger, on straight surfaces, of curved surfaces.



RONG **ON PIPES & CURVED SURFACES**

Powerful magnetic adhesion force

up to max 2248 lbs. (4/5") material thickness /S 275 JR.) Both permanent magnets can be activated with a short turn of the clamping lever. The long set-up surfaces provides optimum adhesion and safety. The pivoting movement of the magnets automatically positions the drilling unit in the central drilling position.

Result: Fast, accurate and safe drilling with the BDS PipeMAB series.

Material thickness and magnetic holding force

Material thickness	1 / $_{3}$ in. (3 mm) 25 / $_{64}$ in (10mm) 25 / $_{32}$ in. (20 mm)		
Maximum magnetic holding force	903 lbs	1962 lbs	2248 lbs

PipeMAB 525		PipeMAB 200
Motor Power	110 V (14.50 Amp)	110 V (8.2 Amp)
Dimensions	20.7"Hx10.5"Lx7.5"W	13.75" H x 10.5" L x 7.5" W
Stroke	6 - ¹ /3"	6- ¹ / ₃ " (3- ¹ / ₃ " with geared chuck
Weight	43 lbs	27 lbs
Speeds	70-280 rpm,180-580 rpm	450 RPM
Arbor Bore	³ /4 ["] Weldon Shank	3/4" Weldon Shank
Magnetic Force (³ / ₄ " plate)	2250 lbs	2250 lbs
Hole Capacity	$2^{-1}/2''$ dia.	1- ³ / ₈ " dia.
Magnet Base Size	10.5" L x 7.5" W x 3.5" H	10.5" L x 7.5" W x 3.5" H
Permanent internal lubrication	n 🔍 🗸	 ✓
Torque control	V	
Full wave control electronics	V	
Overheating protection	V	
Clockwise/anticlockwise rotat	ion 🗸	
Carbon brush wear indicator	V	

Included in delivery		Included in delivery		
1 Magnetic core drilling machine		1 Magnetic core drilling machine		
1 Industrial arbor ZIAL 319KN		1 Ejector pin ZAK 100		
1 Ejector pin ZAK 100 + MT3		1 Safety lashing strap		
1 Safety lashing strap		1 Hexagonal offset screwdriver size 4		
1 Hexagonal offset screwdriver size 5		1 Operating instructions		
1 Operating instructions		1 Plastic carry case		
1 Plastic carry case				
Annular Cutter	Tapping	Annular Cutter		
Up to $\emptyset 2^{-1}/{_2}''$ $\emptyset {}^{15}/{_{16}}''$ dia. Cutter capacity $2^{-1}/{_2}''$	Ø $^{15}/_{16}$ "(Rea m to Ø $^{7}/_{8}$ ")	Ø 1- ³ / ₈ " Cutting depth 2- ⁶¹ / ₆₄ "		
		NITEC		
Drill • Saw • Safety Tools • Finish • Prep • Mix				
1-800-700-5919 (US/CA)	www.csu	nitec.com +1-203-853-9522 (Intl.)		

info@csunitec.com